

## Attention of

: Mr. J. Martinez

## **Analysis Report**

Report number	: 15300/00011231.4/L/22	Submitted date	: 2022-11-12	
Main Object	: Odin Petroil / Análisis Laboratorio	Sample submitted at	: Saybolt Colombia - Cartagena	
Report Date	: 2022-11-15	Date received	: 2022-11-13	
Date of issue	: 2022-11-15	Date completed	: 2022-11-15	
Sample object	: Muestras 13/11/22	Sample number	: 13956054	
Sample type	: Submitted			
Sample submitted as	: Petroil 250 Fuel Oil No 4 Uso Industrial			
Marked	: Petroil 250 Fuel Oil No 4 Uso Industrial			

NAME	METHOD	UNIT	RESULT
API Gravity at 60 °F	ASTM D 1298-12b (2017)	°API	37.0
Density at 15 °C	ASTM D 1298-12b (2017)	kg/m³	839.3
Total Sulfur Content	ASTM D 4294-21	% m/m	<0.012
Corrosion Copper Strip (3 h / 50 °C)	ASTM D 130-19	-	1a
ASTM Color	ASTM D 1500-17	-	L0.5
Kinematic Viscosity at 40 °C	ASTM D 445-21e1	mm²/s	2.026
Water and sediment	ASTM D 1796-11(2016)	% v/v	0.00
Pour Point	ASTM D 97-17b	°C	<-33
Flash Point (PM) - Procedure A	ASTM D 93-20	°C	63.0
Micro Carbon Residue (10% bot.)	ASTM D 4530 / D 86-15 (20)	% m/m	<0.1
Ash Content	ASTM D 482-19	% m/m	<0.010
Distillation	ASTM D 86-20a		
Initial Boiling Point (IBP)		°C	193.5
5% Recovered		°C	200.0
10% Recovered		°C	205.5
20% Recovered		°C	215.5
30% Recovered		°C	222.0
40% Recovered		°C	229.0
50% Recovered		°C	238.0
60% Recovered		°C	244.5
70% Recovered		°C	254.5
80% Recovered		°C	268.0
90% Recovered		°C	285.5
95% Recovered		°C	301.0
Final Boiling Point (FBP)		°C	315.5
Recovery		vol %	98
Residue		vol %	1.5
Loss		vol %	0.5
Heat of Combustion	ASTM D 4868-17		
Gross Heat of Combustion		Btu/lb	19659
Net Heat of Combustion		Btu/lb	18441

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

Saybolt de Colombia SAS, Via Mamonal No. 6-61, Office 206; Cartagena, Republica de Colombia Tel: +57 1 670 6875 Fax: +57 1 670 6845 Website: www.saybolt.com Email: saybolt.colombia@corelab.com All our activities are carried out under Saybolt's terms and conditions, available at www.corelab.com/saybolt/terms-conditions



Attention of

: Mr. J. Martinez

## **Analysis Report**

Report number	<ul> <li>15300/00011231.4/L/22</li> <li>Odin Petroil / Análisis Laboratorio</li> <li>2022-11-15</li> <li>2022-11-15</li> <li>Muestras 13/11/22</li> <li>Ocharitad</li> </ul>	Submitted date	: 2022-11-12
Main Object		Sample submitted at	: Saybolt Colombia - Cartagena
Report Date		Date received	: 2022-11-13
Date of issue		Date completed	: 2022-11-15
Sample object		Sample number	: 13956054
Sample type Sample submitted as Marked	<ul> <li>Submitted</li> <li>Petroil 250 Fuel Oil No 4 Uso Industrial</li> <li>Petroil 250 Fuel Oil No 4 Uso Industrial</li> </ul>		

NAME	METHOD	UNIT	RESULT
FAME content §	EN 14078:2014	% v/v	0.34
Cetane Number §	ASTM D 613	-	43.10
Total aromatics §	ASTM D 6591-19	% v/v	21.0
Stability Test (Reflectance) 90 min §	ASTM D 6468	%	92
Oxidation Stability §	ASTM D 2274-14(2019)	g/m³	1.8
Lubricity by HFRR §	ASTM D 6079-18	μm	494.0

Tests marked with a § are witnessed by Saybolt only.

Saybolt's responsibility is limited to guarantee that:

- the sample tested is the sample as described in this certificate at the date indicated.

- the results reported are the ones actually determined by the laboratory personnel.

The signature of the Saybolt inspector/chemist on site on the laboratory analysis report/certificate issued by the supplier, (or on this form issued by Saybolt as part of the inspection report), by no means is to be considered a guarantee of the correctness of the testing equipment, which remains the sole responsibility of the performing laboratory, but only confirms that the analytical methods used are the ones indicated.

Signed by: Ronald Vargas Barrios - Laboratory Supervisor I Issued by: Saybolt de Colombia SAS Place and date of issue: Cartagena - 2022-11-15

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability for the supplied information. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.